Specifications Model CS-H8c (2K*)

Camera

Image Sensor 1/3" Progressive Scan CMOS

Shutter Speed Self-adaptive shutter

Lens 4mm@ F1.6, viewing angle: 46° (Vertica),

89° (Horizontal), 104° (Diagonal)

6mm@ F1.6, viewing angle:28° (Vertica),

52° (Horizontal), 60° (Diagonal)

PT Angle Pan: 350°, Tilt: 80°

Minimum Illumination 0.5 Lux @ (F1.6, AGC ON), 0 Lux with IR

(Data is obtained from EZVIZ laboratories)

Lens Mount M12

Day & Night IR-Cut filter with auto-switching

DNR 3D DNR

WDR Digital WDR

Night Vision Distance 30 m / 98 ft

Video & Audio

Max. Resolution 2560 × 1440

Frame Rate Max: 30fps; Self-Adaptive during network transmission

Video Compression H.265 / H.264

H.265 Type Main Profile

Video Bit Rate Quad HD; Full HD; Hi-Def; Standard. Adaptive bit rate.

Audio Bit Rate Self-Adaptive

Max. Bitrate 4 Mbps

Network

Wi-Fi Standard IEEE802.11b, 802.11g, 802.11n

Frequency Range 2.4 GHz ~ 2.4835 GHz

Channel Bandwidth Supports 20 MHz

Transmission Rate 11b: 11 Mbps,11g: 54 Mbps,11n: 72 Mbps

Wi-Fi Pairing AP pairing

Protocol EZVIZ Cloud Proprietary Protocol

Interface Protocol EZVIZ Cloud Proprietary Protocol

Wired Network RJ45 × 1 (10M / 100M Adaptive Ethernet Port)

Storage

Local Storage MicroSD card slot (Up to 512GB)

Cloud Storage (Subscription Required)

Function

Smart Alarm Al-Powered Human Shape Detection

Customized Alert Area Supports
Two-way Talk Supports

General Function Anti-Flicker, Dual-Stream, Heart Beat,

Password Protection, Watermark

Preset Locations Supports

Specifications Model CS-H8c (2K+)

General

Operating Conditions $-30~^{\circ}\text{C}$ to 50°C (-22 $^{\circ}\text{F}$ to 122 $^{\circ}\text{F}$), humidity 95%

or less (non-condensing)

IP Grade Weatherproof Design

Power Supply DC 12V / 1A

Power Consumption MAX. 12W

Dimensions $100.05 \times 129.19 \times 149.75 \text{ mm} (3.94 \times 5.09 \times 5.9 \text{ inch})$

Packaging Dimensions $140 \times 140 \times 192 \text{ mm} (5.51 \times 5.51 \times 7.56 \text{ inch})$

Weight (With package) 745 g (26.28 oz) For EU Standard Version

Net Weight 435 g (15.34 oz)

In the box

- H8c 2K+ Camera
- Drill Template
- Screw Kit
- Waterproof Kit
- Power Adapter
- Regulatory Information
- Quick Start Guide

Certifications:

CE / FCC / UKCA / UL / WEEE / RoHS / REACH

Specifications are subject to change without notice. " ** ", " ==zviz-" and other trademarks and logos are the properties of EZVIZ in various jurisdictions.